

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number  
**WO 2004/067935 A1**

(51) International Patent Classification<sup>7</sup>: **F02B 77/13,**  
B60R 13/08

(21) International Application Number:  
PCT/CH2004/000044

(22) International Filing Date: 27 January 2004 (27.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
203 01 200.3 27 January 2003 (27.01.2003) DE

(71) Applicant (for all designated States except US): **RIETER  
TECHNOLOGIES AG [CH/CH];** Schlosstalstrasse 43,  
CH-8406 Winterthur (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **TINTI, Francesco,**  
Carlo [IT/IT]; Via Fiamminghino, 9, I-20156 Milan (IT).

(74) Agent: **SEIFERT, Hans, Ulrich; Felber, Seifert & Part-  
ner, Dufourstrasse 116, P.O. Box 380, CH-8034 Zürich**  
(CH).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: **ENGINE COMPARTMENT PARTITIONING LAYER**



(57) Abstract: For the formation of a sound insulating and absorbing cavity (8) within an engine compartment (1), said engine compartment (1) is partitioned by means of a lightweight engine compartment partitioning layer (7). Said partitioning layer (7) can be made of several sections and forms an essentially cohesive surface within the engine compartment (1). In a preferred embodiment of the invention this partitioning layer (7) consists of a carrier layer (12) and a sound absorbent layer (13) and may comprise first and second water and oil repellent layers (14, 15). The cavity (8) created by this partitioning layer (7) leads to a substantive increase in transmission loss.

JC20 Rec'd PCT/PTO 11 JUL 2005

## ENGINE COMPARTMENT PARTITIONING LAYER

The present invention relates to an engine compartment partitioning layer for use in a motor vehicle engine compartment.

It is the aim of the modern automobile industry to provide vehicles which not only have an acoustically agreeable environment in the passenger compartment, but which also do not emit disturbing noise. In particular the knocking sounds in a low frequency range of 800 – 2000 Hz and other type-specific noise patterns emitted by diesel vehicles are considered undesirable by the automobile industry. Unpleasant noises in the high frequency range of 1000 – 5000 Hz emitted by engine aggregates are also not desirable.

In order to reduce the noise level emitted outwards, and in particular with heavy goods vehicles or trucks, it is known to encapsulate the motor, individual units (for example the gear box or transmission unit), or the whole engine bay, i.e. compartment, by wrapping these in insulating materials. As a rule, acoustically effective linings are provided in the engine compartment of conventional passenger vehicles, and in particular the engine hood and/or front wall is provided with sound damping layers. These linings are essentially in the form of sound insulating parts and only have limited acoustical efficacy.

These measures do not appear to fulfil the acoustic requirements preset by the automobile industry. Any improvement in the acoustic values of these linings results in an increase in thickness and weight of these linings.

It is therefore the aim of the present invention to further reduce noise emitted from the engine compartment in an efficient manner or to eliminate it completely. In particular, it is the aim of the present invention to provide lightweight and acoustically efficient means for reducing the emitted noise.

This is achieved according to the invention with an engine compartment partitioning layer comprising the features of claim 1. In the following, the term "partitioning layer" relates to any

sheet-like component which is arranged between the engine hood and the base section of the engine compartment, and which divides the engine compartment, preferably horizontally.

By means of this partitioning layer an acoustically effective chamber or cavity is developed in the engine compartment with which the energy of the sound field produced by the engine or other vehicle units is diminished by absorbing and insulating effects:

In a preferred embodiment of the invention, this partitioning layer is arranged in such a manner that it lies essentially horizontally, i.e. parallel to the vehicle flooring, and a few centimeters, e.g. 4 – 5 cm, over the engine block. In this way an essentially closed and acoustically effective cavity is formed between the closed engine hood and this partitioning layer. The spatial arrangement of this acoustically effective cavity allows acoustic insulating effects and a number of different absorptive effects to be put to use. It is understood that the dimensions of this cavity can be adjusted by specifically designing the inventive partitioning layer according to particular acoustic requirements. Furthermore this partitioning layer can be provided with additional sound absorbing or heat insulating material in order to achieve a still more efficient solution to the problem.

In particular the acoustically effective cavity created by the engine compartment partitioning layer according to the invention essentially functions in the manner of a large Helmholtz resonator comprising sound absorptive and sound insulating walls. This allows the man skilled in the art to adjust the sound field emitted outwards from the vehicle in an easy and cost-effective way.

In a particular embodiment of the invention the engine compartment partitioning layer is formed of a plurality of mutually complementary sections which are joined together.

In yet another embodiment of the invention a number of engine compartment partitioning layers are arranged in the same engine compartment, thus resulting in the formation of several acoustically effective cavities. In particular, the individual partitioning layers can interact in the manner of Helmholtz resonators.

Other preferred embodiments of or developments to the present invention comprise the features of the dependent claims. In particular, the partitioning layer comprises a carrier layer and a sound

absorbent layer. This carrier layer is made of a compressed phenolic resinous nonwoven layer or a suitable foam material. Preferably, the carrier layer is provided with a first water and oil repellent layer, in particular a textile scrim or felt layer, on the side towards the engine hood. Furthermore, the sound absorbent layer comprises a slightly compressed phenolic resinous layer, in particular a textile scrim or felt layer. It is understood that the expert may choose any suitable sound absorptive material, in particular open celled foams. This sound absorbent layer may be provided with a second water and oil repellent layer, in particular a textile scrim or felt layer, on the side towards the engine compartment floor or the ground.

The partitioning layer can also be made of several joinable and mutually complementary sections if this is suitable for the specific assembly requirements within the engine compartment.

A further development of the partitioning layer according to the invention foresees at least one acoustically effective aperture in order to increase the acoustic absorptive effects related to Helmholtz resonators. In addition, these apertures may also serve to drain water or oil residues or other liquid waste material out of the cavity. The expert may also consider to form a plurality of such cavities within the engine compartment, which cavities may have differing volumes in order to tune the acoustic properties.

Regarding the properties that influence the overall acoustic performance of a vehicle, transmission loss and absorption coefficient, and considering the improvement in transmission loss as of secondary importance, the use of an engine compartment partitioning layer according to the invention effectively reduces the acoustic energy leakage out of the engine compartment. Measurements prove that the absorption coefficient of a configuration according to the present invention shows a considerable increase in the frequency ranges between 100 – 400 Hz and 1000 – 5000 Hz. The improvements at higher frequencies can be related to the airflow resistance of the scrim layer, while the improvements in the lower frequency range are essentially due to the absorptive effect of the cavities.

The invention is described in more detail by way of an exemplary embodiment and with the aid of the Figures.

Fig. 1 shows a schematic cross-section of an engine compartment with a conventional sound absorbing lining according to the state of the art;

Fig. 2 shows a schematic cross-section of an engine compartment having a partitioning layer according to the invention;

5 Fig. 3 shows a schematic cross-section of an engine compartment comprising a partitioning layer according to the invention in greater detail than shown in Fig. 2; and

Fig. 4 is a diagram showing the frequency dependence of the absorption coefficient of a configuration according to the invention.

10

The schematic cross-section according to Figure 1 shows an engine compartment 1 in which an engine 2 and a vehicle unit or aggregate 3 are arranged. This engine compartment 1 is provided with sound damping linings, and in particular with a front wall lining 4 and an engine hood lining 5. Vehicles are also known which have an engine floor lining 6. Such linings are well known to the expert and are not the object of the present invention.

15

The schematic cross-section according to Figure 2 shows an engine compartment 1 which is equipped with an engine compartment partitioning layer 7 according to the present invention. On the one hand, this partitioning layer 7 lies immediately above the engine 2 and, on the other hand, 20 forms an essentially closed, acoustically effective cavity 8 in the closed engine compartment 1. In a preferred embodiment of the invention, this partitioning layer 7 is dual layered and comprises on the engine hood side a carrier layer 12, in particular a compressed felt layer containing phenolic resin and is provided with a first water and oil repellent layer 14, in particular a textile scrim, nonwoven or felt layer. Towards the engine compartment floor or towards the ground the dual 25 layered partitioning layer 7 comprises a second water and oil repellent layer 15, in particular a slightly compressed felt layer (sound absorptive layer) containing phenolic resin. Furthermore, the engine compartment 1 shown in Figure 2 has a conventional engine hood lining 5 and a conventional front wall lining 4. By adding a second partitioning layer 9 a second cavity 10 is formed, or a third cavity 11, if the engine compartment 1 is provided with a floor lining 6. These 30 partitioning layers (6, 7, 9) are designed in such a manner that they can follow the contours of the engine 2 or other vehicle units or aggregates 3 in the engine compartment 1. They may also be designed in such a manner that openings in these partitioning layers allow the individual units or aggregates to protrude through these in a close fitting manner, i.e. in a collar-like manner.

It is to be understood that the partitioning layers 7, 9 according to the invention are formed in such a manner that they can be easily removed from the engine compartment 1 for purposes of vehicle maintenance. The partitioning layers 7, 9 can preferably be made by joining several sections.

Suitable joining means are well known to the person skilled in the art.

Figure 3 shows a more detailed schematic view through an engine compartment 1 containing an engine 2 and with a preferred arrangement of the inventive partitioning layer 7. Here, the partitioning layer 7 is arranged on top of the engine and, together with the closed engine hood 17, forms an acoustically effective cavity 8. This partitioning layer 7 consists of a carrier layer 12 and a sound absorbent layer 13. Preferably this dual layered construction comprises a first water and oil repellent layer 14 on the engine hood side as well as a second water and oil repellent layer 15 on the side toward the engine compartment 1 or the ground. Preferably the engine hood 17 is covered on the engine side with a conventional lining material 18. It has proven to be advantageous to foresee a thin air layer between the first and/or second water and oil repellent layers 14, 15 and the partitioning layer 7. This Figure further shows an optional, acoustically effective aperture 16, which might also serve to drain liquid waste material. It is within the skill of the expert to choose suitable materials for designing the inventive engine compartment partitioning layer 7.

Figure 4 shows a diagram of the frequency dependence of the absorption coefficient of a configuration according to the invention. The specific configuration used for calculating the acoustic properties, in particular the absorption coefficient, is as follows:

- a 0.8 mm thick steel plate (representing the engine hood),
- a 0.001 mm deep air space,
- a 1 mm thick lining material,
- a 20 – 50 mm deep air space (representing the cavity),
- a 1 mm thick first water and oil repellent layer, made of 100 g/m<sup>2</sup> PET felt plus 20 g/m<sup>2</sup> thermoplastic adhesive (e.g. SURLYN®)
- a 4 mm thick carrier layer made of 1200 g/m<sup>2</sup> phenolic felt
- a 20 mm thick sound absorbent layer made of 500 g/m<sup>2</sup> PET felt, covering 80% of the total surface;

- a 1 mm thick second water and oil repellent layer, made of 80 g/m<sup>2</sup> PET felt plus 20 g/m<sup>2</sup> thermoplastic adhesive.

This arrangement corresponds to the arrangement shown in Figure 3. The values of the frequency dependent absorption coefficient related to this arrangement are shown in curve A of Figure 4.

5

In order to demonstrate the performance of the inventive concept, comparative calculations were made for a conventional multilayer hood liner comprising:

- a 0.8 mm thick steel plate;
- a 0.001 mm thin air layer;
- 10 - a 20 mm thick absorptive layer (Thinsulate™, covering 80% of the total surface);
- a 4.7 mm thick compressed felt (carrier)

The values of the frequency dependent absorption coefficient related to this comparative arrangement are shown in curve B of Figure 4.

15

Finally, curve C of Figure 4 shows the values of a simple 20 mm thick standard felt, which curve makes obvious the improvement obtained by the present invention.

20

The advantages of the inventive engine compartment partitioning layer are immediately evident and are to be seen in particular in the reduction of sound emission towards the vehicle exterior in the desired frequency range, such as occurs in city traffic with a loaded or unloaded vehicle. This reduction in sound emission is a result of the increased transmission loss caused by the inventive partitioning layer. It is to be understood that by using several partitioning layers these annoying sound emissions can be further reduced. In particular, the acoustic efficacy of the individual cavities formed according to the invention can be optimized by suitable design and by providing further acoustically efficient lining parts as well as by providing suitable acoustically effective apertures in the individual partitioning layers.

25

A further advantage is to be seen in the weight reduction as compared to conventional liner concepts. In particular, the use of such lightweight partitioning layers allows to replace conventional heavy layer damping materials

30

First measurements of such a configuration have shown that use of a partitioning layer 7 has led to a reduction in the emitted sound level (an increase of transmission loss) of approx. 4 dB in the range of 800 – 2000 Hz.

- 5 During these measurements, the absorption coefficient in this frequency range was between 0.2 and 0.85. A dual layered partitioning layer 7 was used for these measurements, whose carrier layer 12 had a density of  $450 \text{ kg/m}^3$  and an air flow resistance of 2400 Rayls and whose absorbent layer 13 had a density of  $80 \text{ kg/m}^3$  and an air flow resistance of 600 Rayls.
- 10 Further developments of the partitioning layer according to the invention can comprise heat protective, sound absorptive or electrically conductive elements.



## Patent Claims

1. Engine compartment partitioning layer (7) for use in an engine compartment (1),  
5 wherein said partitioning layer (7) partitions the engine compartment (1) and forms at least one acoustically effective cavity (8) within the closed engine compartment (1).
2. Partitioning layer (7) according to claim 1, wherein said partitioning layer (7) consists of a carrier layer (12) and a sound absorbent layer (13).
3. Partitioning layer (7) according to claim 2, wherein said carrier layer (12) comprises a  
10 compressed phenolic resinous nonwoven layer.
4. Partitioning layer (7) according to claim 3, wherein said carrier layer (12) is provided with a first water and oil repellent layer (14), in particular a textile scrim or felt layer, on the engine hood side.
5. Partitioning layer (7) according to claim 2, wherein the sound absorbent layer (13)  
15 comprises a slightly compressed phenolic resinous layer, in particular a textile scrim or felt layer.
6. Partitioning layer (7) according to claim 5, wherein the sound absorbent layer (13) is provided with a second water and oil repellent layer (15), in particular a textile scrim or felt layer, toward the engine compartment floor or the ground.
- 20 7. Partitioning layer (7) according to one of claims 1 to 6, wherein said partitioning layer (7) is made of several joinable and mutually complementary sections.
8. Partitioning layer (7) according to one of claims 1 to 7, wherein said partitioning layer (7) is provided with at least one acoustically effective aperture (16).
9. Use of an engine compartment partitioning layer (7) according to claim 1 within an  
25 engine compartment (1).
10. Use of several engine compartment partitioning layers (7, 9) according to claim 1 within an engine compartment (1) for forming a plurality of acoustically effective cavities (8, 10) within the engine compartment (1).
- 30 11. Use of several engine compartment partitioning layers (7, 9) according to claim 9, wherein said cavities (8, 10) have differing volumes.

1/2




Fig. 1




Fig. 2

2/2




Fig. 3




Fig. 4

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/CH2004/000044

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 F02B77/13 B60R13/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 F02B B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 966 799 A (ROHRER PAUL ET AL) 30 October 1990 (1990-10-30)	1-3,5; 9-11
Y	column 2, line 37 -column 5, line 15; figures 1,3	4,6
X	US 5 567 922 A (SCHMUCK JEAN-CLAUDE ET AL) 22 October 1996 (1996-10-22)	1,2,5-11
Y	column 3, line 39 -column 5, line 37; figures 1,3-5	4,6
X	WO 97/48576 A (KWON HOE HYON ;DAEHAN CHEMICAL IND CO LTD (KR)) 24 December 1997 (1997-12-24) page 3, line 1 -page 5, line 20; figure 3	1,2,5, 7-11
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

27 April 2004

Date of mailing of the international search report

11/05/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Nobre, S

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/CH2004/000044

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 004, no. 154 (M-038), 28 October 1980 (1980-10-28) & JP 55 104528 A (ASAHI FIBER GLASS CO LTD), 11 August 1980 (1980-08-11) abstract; figures 1-4 -----	1,2,8-11

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CH2004/000044

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4966799	A	30-10-1990	CH 671546 A5 AT 61283 T BR 8704956 A DE 3768401 D1 EP 0262092 A1 ES 2021392 T5 FI 874206 A JP 2788958 B2 JP 63102925 A MX 170771 B	15-09-1989 15-03-1991 17-05-1988 11-04-1991 30-03-1988 16-01-2000 27-03-1988 20-08-1998 07-05-1988 14-09-1993
US 5567922	A	22-10-1996	CH 684398 A5 US 5741390 A AT 116606 T DE 59201115 D1 EP 0511157 A1 ES 2067319 T3 JP 3291565 B2 JP 6171436 A	15-09-1994 21-04-1998 15-01-1995 16-02-1995 28-10-1992 16-03-1995 10-06-2002 21-06-1994
WO 9748576	A	24-12-1997	KR 235678 B1 WO 9748576 A1	15-12-1999 24-12-1997
JP 55104528	A	11-08-1980	NONE	